



Be Right™



## LT200 Dry thermostat with 2 blocks, 15 x 13 mm, 6 x 13 mm / 4 x 20 mm

Product #: LTV082.99.21002

GBP Price: Contact Us  
Available

### Thermostat for standard and special digestions

Pre-programmed for all standard digestions and freely programmable for user specific digestions

2 separate controllable heating blocks with separate protection covers, left block 15x13mm holes, right block 6x13mm and 4x20mm holes

illuminated digital display for remaining time/temperature and operator guidance

3 pre-programmed and 6 freely programmable storage spaces

Temperature settings between 37 °C and 150 °C in 1 °C steps, time setting between 1 and 480 min

### Great flexibility

### Excellent reproducibility

### Simple to use

---

## Specifications

Display resolution:	5 x 7 dot matrix
Display size:	2 x 16 characters
Display type:	LCD
Heating programmes:	Pre-programmed for 40°C, 100°C, 148°C and freely selectable from 37-150°C, 1-480 min
Heating rate:	from 20 to 148 °C in 10 minutes
Manual languages:	English, French, German, Italian, Spanish, Dutch, Swedish, Danish, Polish
Max. operating humidity:	90 %
Number of cuvettes:	21 x 13 mm diameter
Number of cuvettes (2):	4 x 20 mm diameter
Operating temperature range:	10 - 45 °C
Power requirements (Voltage):	115/220 V AC
Power supply:	115 V - 230 V +5%/-15%, 50 - 60 Hz, 900 VA max
Safety checks:	CE, GS, cTUVus
Storage conditions:	-40 - 60 °C

Temperature stability:	± 1 °C in conformity with EN, ISO, EPA methods
User interface:	3 softkeys
User programmes:	6 free temperature/time
Warranty:	2 years
Weight:	2.8 kg